

Keyed Flanges:



HD408 Original Factory Flange Specifications

Keyed Flanges:

- No. 0: Minimum Diameter: 26mm Keyway: 5mm
- No. 1: Minimum Diameter: 23.16mm Keyway: 5mm
- No. 2: Minimum Diameter: 20.5mm Keyway: 5mm
- No. 3: Minimum Diameter: 20mm Keyway: 4.76mm
- No. 13: Minimum Diameter: 23mm Keyway: 4.8mm

Splined Flanges:



Get Spline Major Diameter & Number of Teeth

The steering wheel flange of the original tractor, as shown in the figure , has a tooth count of 18.

HD408 Original Factory Flange Specifications

Splined Flanges:

No. 4: Spline Major Diameter: 20.77mm Number of Teeth: 36

No. 5: Spline Major Diameter: 16.09mm Number of Teeth: 36

No. 6: Spline Major Diameter: 20.07mm Number of Teeth: 36

No. 7: Spline Major Diameter: 18.6mm Number of Teeth: 36

No. 8: Spline Major Diameter: 18.02mm Number of Teeth: 36

No. 10: Spline Major Diameter: 17.69mm Number of Teeth: 40

No. 11: Spline Major Diameter: 20.07mm Number of Teeth: 36

No. 12: Spline Major Diameter: 16.09mm Number of Teeth: 36

No. 20: Spline Major Diameter: 15.17mm Number of Teeth: 18

No. 21: Spline Major Diameter: 14.86mm Number of Teeth: 30

No. 22: Spline Major Diameter: 15.7mm Number of Teeth: 30